

RdnId

X.500.

enum	<pre>Type { commonName = rt_pc_x500_rdn_nid_common_name, surname = rt_pc_x500_rdn_nid_surname, givenName = rt_pc_x500_rdn_nid_given_name, title = rt_pc_x500_rdn_nid_title, pseudonym = rt_pc_x500_rdn_nid_pseudonym, emailAddress = rt_pc_x500_rdn_nid_email_address, countryName = rt_pc_x500_rdn_nid_country_name, localityName = rt_pc_x500_rdn_nid_locality_name, stateOrProvinceName = rt_pc_x500_rdn_nid_state_or_province_name, organization = rt_pc_x500_rdn_nid_organization, organizationalUnit = rt_pc_x500_rdn_nid_organizational_unit, street = rt_pc_x500_rdn_nid_street, ogrn = rt_pc_x500_rdn_nid_ogrn, ogrnip = rt_pc_x500_rdn_nid_ogrnip, snils = rt_pc_x500_rdn_nid_snils, inn = rt_pc_x500_rdn_nid_inn }</pre>
------	---

enum rutoken::pkicore::X500Dn::RdnId::Type

commonName	
surname	
givenName	
title	
pseudonym	
emailAddress	
countryName	
localityName	
stateOrProvinceName	
organization	
organizationalUnit	
street	
ogrn	
ogrnip	
snils	
inn	